

**INTRODUCING**

**KURO**

**LIMITED EDITION**

**SA223 TRACTOR**

**SERIOUS TRACTION. SMARTER CONTROL. BETTER COMFORT.  
THE KURO WORKS HARDER—AND LOOKS SHARPER DOING IT.**





# SA223 KURO

Featuring dual-range speeds, standard differential lock, and true position control on the 3-point lift system, the KURO is powered by Yanmar's legendary 3-cylinder, liquid-cooled diesel engine paired with a hydrostatic transmission. It's the perfect combination of power, functionality, and precision.

A standout in its field, the KURO comes equipped with crossover hybrid tires to handle more challenging terrain, plus the added comfort of an ergonomic, contoured suspension seat, and a standout grill that shows you mean business.



## SPECIFICATIONS

Ideal Acreage	Under 25
Engine HP	21.5
Loader Lift Capacity	825 LBS at Pivot Pins
Transmission	Hydrostatic

### WARRANTY COVERAGE

Tractor*	24 months or 2,000 hours (whichever comes first)
Powertrain*	10 years or 3,000 hours (whichever comes first)

\*for non-commercial, home and residential use only

### POWERTRAIN

Engine Manufacturer	Yanmar
Engine Gross Power	21.5 HP (16.0 kW)
PTO Power	15.6 (11.6 kW)
Rated Engine Speed	3,200 RPM

### CAPACITIES

Fuel Tank	6.1 gal. (23 L)
-----------	-----------------

### DRIVETRAIN

Transmission Type	Hydrostatic
Rear Differential Lock	Foot Pedal Engagement
2WD/4WD Engagement	Selectable
PTO Type	Hydraulic Clutch
PTO Control	Position Control, Open Center
Rear PTO Speed	540 RPM

### HYDRAULICS

Pump Capacity (Steering) @ Rated RPM	3.7 GPM (14.1 L/min)
Pump Capacity (Implement) @ Rated RPM	4.3 GPM (16.1 L/min)
3-Point Hitch Category	Limited Category 1
3-Point Lift Capacity at 24" (61 cm)	600 lbf. (300 kgf)
Remote Valves	Optional (1 or 2)
3rd Function Valve	Optional

### DIMENSIONS AND WEIGHT

Minimum Ground Clearance	6.4" (163 mm)
Total Weight	1,537 lb. (697 kg)

### FRONT END LOADER

#### YL110

Maximum Lift Height to Pivot Pin	71" (1,800 mm)
Lift Capacity to Maximum Height at Pivot Pin	825 lb. (375 kgf)
Breakout Force at Ground Level Pivot Pins	1,342 lb. (610 kgf)





## LIFT MORE WITH A LONGER WARRANTY

**BUILT BETTER.  
BACKED LONGER.**  
Industry-leading warranty.



**8 YEARS**  
2018-25  
EQUIPMENT DEALERS ASSOCIATION  
SURVEY | TRACTOR MANUFACTURERS

**PRODUCT  
QUALITY**

Find your local dealer at  
[yanmartractor.com/dealer-locations](http://yanmartractor.com/dealer-locations)  
or by visiting:



- [facebook.com/yanmartractoramerica](https://facebook.com/yanmartractoramerica)
- [instagram.com/yanmartractorsamerica](https://instagram.com/yanmartractorsamerica)
- [linkedin.com/yanmaramerica](https://linkedin.com/yanmaramerica)
- [youtube.com/user/yanmarusa](https://youtube.com/user/yanmarusa)



YANMAR America Corporation  
101 International Pkwy, Adairsville, GA 30103  
770.877.9894

[www.YanmarTractor.com](http://www.YanmarTractor.com)

The information in this brochure is accurate as of the date of printing and subject to change. All rights reserved by and belong to YANMAR®. ©2025 YANMAR America Corporation.

YANMAR has a corporate policy of continuous product improvement and development; therefore data, specifications, and warranty are subject to change without any advance notice. There may be differences between the specifications and illustrations contained in this publication and the actual equipment. Equipment components produced by other manufacturers may be shown in photographs in this publication for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. Inspect equipment before using it and be sure it is operating properly. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating a machine, read, understand, and follow all instructions of the manual and on the machine. YANMAR disclaims all representations, express or implied, or any liability from the use of this publication.

